
Technical Information

How the energy from a vehicle impact is calculated




½ Mass x Speed² = Joules

Tested Impact Energy

8,800 Joules

Equivalent vehicle and speed




10 tonne X 3 mph impact

90° Impact on Bollard


Impact Test

Max Energy (Joules) at 90° 8,800

Deflection at Max Energy
15° Lean




Force to Bolt
35kN



Material Properties	MEMAPLEX™
Temperature Range	-10°C to 50°C
Ignition Temperature	370°C to 390°C
Flash Point	350°C to 370°C
Toxicity	Not Hazardous
Chemical Resistance	Excellent - ISO/TR 10358
Weathering Stability (Grey Scale)	5/5*
Light Stability (Blue Wool Scale)	7/8**
Static Rating (Surface Resistivity)	1015 - 1016 Ω
Hygiene Seals	No

* Weathering scale 1 is very poor and 5 is excellent
** Light stability scale 1 is very poor and 8 is excellent

Dimensions (mm)



Bollard Options



Standard Yellow
RAL 1007*
PANTONE 7548*



Standard Grey
RAL 9007*
PANTONE
Cool Grey 5*

Colour Combinations

*Please note that the RAL and PANTONE colours listed are the closest match to standard A-SAFE colours, but may not be exact matches of the actual product colour and should be used for guidance only.

A-SAFE Est. 1984

iFlex™

Heavy Duty Bollard



Designed to protect against damage caused by heavier weight vehicles or in higher speed environments.

The iFlex Heavy Duty Bollard is designed to protect structures and equipment from impact damage. Providing a robust physical presence to prevent access and guide vehicles.

Strong, durable and highly visible, A-SAFE Heavy Duty Bollards permanently reinforce a driver's attention to safe driving and provide enhanced protection against significant damage to property.

TÜV NORD
TÜV NORD Systems GmbH & Co. KG
Freiwillige Prüfung
Prüfbescheinigung PP7001 - 28.01.2013 / 13264001.30
A-SAFE PENDULUM IMPACT TESTED

Code of Practice for Workplace Safety Barriers
PAS13

A-SAFE Headquarters
Habergham Works, Ainleys Industrial Estate, Elland, HX5 9JP, West Yorkshire, United Kingdom.
www.asafe.com

PROTECT SAFE SYSTEM
0739.646.666 - office@protectsafe.ro

Engineered for performance

A-SAFE's state of the art products are meticulously engineered to deliver the highest performance. Designed, developed, tested and manufactured in-house at our cutting-edge facility, each unique component is carefully crafted and purpose-built to play a vital role in the product's performance.


Advanced strength polymer created from an exclusive composition of the most sophisticated polyolefins and rubber additives, expertly blended for unequalled strength and flexibility.

Unrivalled recovery through a unique built-in memory that allows the material to flex, cushion and reform repeatedly upon impact, saving vast amounts in bollard and vehicle repairs.

Huge return on investment from incident prevention and downtime avoidance as bollards, vehicles, floors and equipment do not need replacing or repair.


Self coloured and UV stabilised for continued high visibility and long lasting aesthetics with no repainting.


Energy absorbent foam creates permanent contact cushion between the internal and external structures.



MEMAPLEX™


Patented Engineering Molecular reorientation during manufacturing creates a unique built-in memory that enables the bollard to fully recover following impacts.





Revolutionary 3-Layered Material

- Inner strengthening core
- Central impact absorption zone
- Outer UV stabilised colour layer



Galvanised Steel Heavy duty 15mm thick galvanised base plate minimises the risk of floor damage; reducing maintenance requirements.


In-line coupling for height flexibility

The iFlex in-line coupling introduces a new level of modularity to the vertical height of a range of A-SAFE products. The coupling enables customers to take the standard 1200mm bollard up to 2000mm.

Four pin positioning to top and bottom sections gives increased rigidity and stability.

Seamless join enables easy stacking of top and bottom bollard sections.

Moulded pins lock securely into the internal layer with a quarter turn.



Rotating wear collar for advanced deflection


The wear collar adds an extra layer of protection along the full height of the bollard.

The rotating action deflects force from repeat glancing blows. Preventing expensive on-going maintenance costs.



High impact core

Heavy duty or high speed vehicles present greater risk of impact damage. The extended height galvanised core provides enhanced impact protection.





Higher level bollards give a strong visual alert for reversing HGV drivers, preventing costly damage to service yard infrastructure.



Ideal for use on vehicle routes with sharp angle turns such as car parks.



Protect vulnerable access points where heavy duty vehicles are in operation.